

AXIS FA51 Main Unit

Single-channel main unit with HDMI output

This modular single-channel main unit can connect to one sensor unit offering highly discreet surveillance. Featuring an HDMI output, it's possible to display live video on a public viewing monitor. And, AXIS Face Detector highlights faces within bounding boxes to let would-be shoplifters know they're being monitored and proactively reduce shoplifting. Compatible with all AXIS FA sensor units including IR sensor units, you'll enjoy excellent video quality even in complete darkness. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network.

- > **HDTV 1080p at full frame rate**
- > **AXIS Face Detector preinstalled**
- > **HDMI output for public viewing monitors**
- > **2 configurable input/output ports**
- > **Compatible with all AXIS FA sensor units**



AXIS FA51 Main Unit

System on Chip (SoC)		Casing	IP4X- Aluminum casing Color: black NCS S 9000-N
Model	ARTPEC-6	Sustainability	PVC free, BFR/CFR free
Memory	1024 MB RAM, 512 MB Flash	Power	Power over Ethernet (PoE) IEEE 802.3af Type 1 Class 3, typical 5.2 W, max 6.82 W
Video		Connectors	RJ45 10BASE-T/100BASE-TX PoE RJ12 for sensor unit 4-pin terminal block for two configurable alarm inputs/outputs (12 V DC output, max. load 50 mA) HDMI type D
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Resolution	1920x1080 (1080p) to 160x90	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Maximum temperature (intermittent): 60 °C (140 °F) Start-up temperature: -20 °C (-4 °F) Humidity 10–85% RH (non-condensing)
Frame rate	Up to 25/30 fps in all resolutions	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–85% RH (non-condensing)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 HDMI	Approvals	EMC EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1 Environment IEC/EN 60529 IP4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267
HDMI output	Single camera source Playlist: single camera sources, still images 1080p 30/25/24 fps (50/60 Hz) 720p 50/60 fps (50/60 Hz) 576p 50 fps (50/60 Hz) 480p 60 fps (50/60 Hz)	Dimensions	24 x 49 x 152 mm (0.9 x 1.9 x 6.0 in)
Image settings	Contrast, brightness, sharpness, white balance, exposure control, exposure zones, compression, rotation: 0°, 90°, 180°, 270° including corridor format, mirroring, polygon privacy mask, control queue	Weight	195 g (0.43 lb)
Pan/Tilt/Zoom	Digital PTZ, preset positions	Included accessories	Installation guide, Windows® decoder 1-user license, terminal block connector
Network		Optional accessories	AXIS T8415 Wireless Installation Tool, AXIS Surveillance Cards, AXIS T8120 Midspan 15 W 1-port For more accessories, see axis.com
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, multi-level user, brute force delay protection, signed firmware, secure boot, Axis Edge Vault with Axis device ID	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, RTCP, DHCP, SOCKS, SSH, MQTT	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
System integration		Warranty	5-year warranty, see axis.com/warranty
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G and ONVIF [®] Profile S, specification at onvif.org	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>	
Event conditions	Device status, edge storage, I/O, PTZ, scheduled event, video	Environmental responsibility: axis.com/environmental-responsibility	
Event actions	Toggle I/O, send images, publish MQTT, send notifications, overlay text, recordings, SNMP trap messages, status LED, video clips		
Data streaming	Event data		
Analytics			
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, AXIS Face Detector, active tampering alarm Supported AXIS People Counter, autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap		
General			