

AXIS Camera Station S1116 MT Recorder

Out-of-the box ready server and client for UHD surveillance

AXIS Camera Station S1116 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. For quick and easy installation, AXIS S1116 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With enterprise-grade hard disks, operating system stored on solid-state drive (SSD), and expandable storage capacity, AXIS S1116 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



AXIS Camera Station S1116 MT Recorder

Licenses	16 AXIS Camera Station core licenses included, can be upgraded up to 32 licenses (sold separately)	4 x 1080p camera split views or 1 x 4K camera view Supports two monitors.
Hardware		Recording
Processor	Intel® Core™ i5	Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.
Memory	8 GB	General
Storage	Enterprise Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 8 TB (1x8 TB)	Operating system
RAID	RAID levels: 0, 1	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 128 GB SSD
Graphic card	Intel® HD Graphics	Operating conditions
Power	360 W (100 - 240 V AC, 50/60 Hz, 5.0 - 2.5 A)	0 °C to 45 °C (32 °F to 113 °F)
Connectors	Front side: 1x Universal audio jack 2x USB 2.0 1x USB 3.1 1x USB 3.1 Type-C Rear side: 2x USB 2.0 4x USB 3.1 2x DisplayPort™ 1.2 1x Ethernet (RJ45) 1 GbE 1x Audio line out 1x Serial port	Storage conditions
Video		-40 °C to 65 °C (-40 °F to 149 °F)
Video streaming	Live view: Up to 25 camera split views or 1 x 4K camera view Playback:	Approvals
		EMC EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 50564, EN 62623, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KN35, Safety IEC/EN/UL 60950-1, NOM, BSMI, EAC
		Dimensions
		274 x 154 x 350 mm (10.8 x 6.1 x 13.8 in)
		Weight
		7.4 kg (16 lb)
		Included accessories
		Power cord, keyboard, mouse
		Optional accessories
		Axis joysticks and control boards For more accessories, see axis.com
		Warranty
		5-year warranty, see axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility