

AXIS T8508 PoE+ Network Switch

8-port switch for efficient network management

AXIS T8508 PoE+ Network Switch is an 8-port managed Gigabit switch with a compact, fan-less design for installation in noise sensitive environments or to be used as an edge switch. AXIS T8508 is a perfect complement to Axis' recorders to further simplify setup and installation of surveillance systems. The intuitive administrator interface offers a graphic topology for easy overview of all devices in the system with information about connected devices and status. The high PoE power output allows for connection of up to 8 PoE cameras.

- > **30 W PoE per port, total 130 W**
- > **Gigabit switch**
- > **2 SFP/RJ45 Combination Ports**
- > **Intuitive graphic topology for system overview**



AXIS T8508 PoE+ Network Switch

Network		Power
Network function	DHCP server included VLAN	Power connector port
Security	Password protection, IP address filtering, HTTPS encryption, IEEE 802.1X network access control, ACL, Private VLANs, DHCP Snooping	Surge protection 6kV on all network ports and AC lines
Supported protocols	IPv4, IPv6, HTTP, HTTPS, QoS, Bonjour, UPnP, SNMP v1/v2c/v3, DNS, NTP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SSH, STP, RSTP, MSTP, LLDP, LLDP-MED, TFTP, SMTP, BPDU	Operating conditions 0 °C to 50 °C (32 °F to 122 °F) Humidity 10–90% RH (non-condensing)
Throughput	14.9 Mpps	Storage conditions -10 °C to 70 °C (14 °F to 158 °F) Humidity 5–95% RH (non-condensing)
Switching capacity	20 Gbps	Approvals EMC EN 55032 Class A EN 55024 FCC part 15 Subpart B Class A VCCI Class A RCM AS/NZS CISPR 32 Class A ICES-003 Class A Safety IEC/EN/UL 60950-1 EAC CE, ITE, JATE
MAC table	8 K	Management software AXIS Device Manager
Jumbo frames	9216 Bytes	Included accessories Installation Guide Drill template Power cord Rubber feet (4x)
General		Optional accessories AXIS T85 Rack Mount Kit A
Casing	Metal Color: Black	Warranty 5-year warranty, see axis.com/warranty
Environment	Indoor	Environmental responsibility: axis.com/environmental-responsibility
Dimensions	WxDxH: 220 x 242 x 44 mm (8.6 x 9.52 x 1.73 in)	
Weight	2.1 kg (4.63 lbs)	
Power requirements	100–240 V AC, 50/60 Hz	
PoE class	Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4	
PoE output	Port 1 to 8: Up to 30 W Power budget: 130 W	
Connectors	PoE ports RJ45 10Base-T/100Base-TX/1000Base-T (8x) Uplink Combination port RJ45/SFP 100Base-TX/1000Base-T (2x)	