

AXIS C1610-VE Network Sound Projector

Sleek, robust speaker for clear speech

This network sound projector features a clean and minimalistic design suited to both outdoor and indoor environments. Digital signal processing (DSP) ensures clear sound, and embedded audio management software lets users remotely coordinate security, safety, and operational messages alongside background music. Built-in memory supports prerecorded messages, and live speak lets personnel address events in real time. Built on open standards, this speaker supports integration with network video, access control, analytics, and VoIP (supporting SIP). This standalone unit connects directly to your standard network for a flexible, scalable, cost-effective audio solution. Furthermore, its IK10 vandal-resistant rating allows for placement almost anywhere.

- > [Sleek, vandal-resistant design](#)
- > [All-in-one, outdoor-ready speaker system](#)
- > [Connects to standard network](#)
- > [Simple installation with PoE](#)
- > [Remote health testing](#)



AXIS C1610-VE Network Sound Projector

Audio hardware		Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32	
Enclosure	One-way enclosure with 4-inch broadband dynamic cone speaker	Intelligent audio Auto Speaker Test	
Max sound pressure level	106 dB	Event triggers Virtual inputs, External input Call: DTMF, State changes, AXIS Camera Application Platform (ACAP)	
Frequency response	200 Hz - 16 kHz	Event actions File upload: HTTP, network share and email Notification: email, HTTP and TCP Play audio clip Perform Auto Speaker Test Send SNMP trap Status LED	
Coverage pattern	130° (at 2 kHz)	Built-in installation aids Test tone verification and identification	
Audio input/output	Built-in microphone (can be disabled mechanically)	Functional monitoring Auto Speaker Test, Connection verification, Built-in system logging	
Built-in microphone specification	50 Hz - 15 kHz	General	
Digital signal processing	Built-in and pre-configured	Casing Impact-resistant aluminum, IP66-, IK10-, NEMA 4X-, and MIL-STD-810G 509.5-rated.	
Amplifier description	Built-in 7 W Class D amplifier	Power Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 (max. 12.95 W)	
Audio management		Connectors RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block with two I/Os	
AXIS Audio Manager Edge	Built-in: – Content management for music and live/pre-recorded announcements. – Scheduling to decide when and where to play specific content. – Content prioritization to ensure urgent messages interrupt the schedule. – Zone management allowing you to divide up to 200 speakers into 20 zones. – Health monitoring for remote discovery of system errors. – User management to control who has access to what features. See separate datasheet for more details.	Reliability Designed for 24/7 operation.	
AXIS Audio Manager Pro	For larger and more advanced systems. Sold separately. See separate datasheet for specifications.	Operating conditions -40°C to 55 °C (-40 °F to 131 °F) Humidity 10-100% RH (condensing)	
Audio software		Storage conditions -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (condensing)	
Audio streaming	One-way/two-way with optional half-duplex echo cancellation. Mono.	Approvals EMC EN 55032 Class B, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KC KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22 Environment IEC 62262 IK10, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 60529 IP66, NEMA 250 Type 4X, MIL-STD-810G 509.5	
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis μ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.	Dimensions Ø203 X 105 mm (Ø8.0 x 4.1 in)	
System on chip (SoC)		Weight 4.1 kg (9.0 lb)	
Model	i.MX6 SX	Included accessories Installation Guide, AVHS Authentication Key, AXIS Camera Station license key, AXIS Connector Guard A, Cable shoe	
Memory	512 MB RAM, 512 MB Flash	Optional accessories AXIS T91B47 Pole Mount, AXIS T91F67 Pole Mount, Cable Gland M20x1.5, RJ45, Cable Gland A M20, AXIS Power over Ethernet Midspans, T94R01B Corner Bracket, T94P01B Corner Bracket, T94S01P Conduit Back Box For more accessories, see axis.com	
Network		Video management software AXIS Camera Station, Video management software from Axis' Application Development Partners available on axis.com/techsup/software	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Languages English, German, French, Spanish, Italian	
Network protocols	IPv4/v6, HTTP, HTTPS ^a , SIP, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, TCP, UDP, IGMPv1/v2/v3, ICMP, DHCP, ARP, SOCKS, SSH	Warranty 5-year warranty, see axis.com/warranty	
System integration		Warranty 5-year warranty, see axis.com/warranty	
Application Programming Interface	Open API for software integration, including VAPIX [®] . One-click cloud connection, AXIS Camera Application Platform (ACAP).	Warranty 5-year warranty, see axis.com/warranty	
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN)	Warranty 5-year warranty, see axis.com/warranty	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility