

QND-8011

5M H.265 NW Dome Camera(Q mini)



Key Features

- Max. 5Megapixel (2592 x 1944) resolution
- 2.8mm fixed lens
- 0.15Lux (Color), WDR (120dB)
- Max. 30fps@5MP (H.265 / H.264)
- H.265, H.264, MJPEG codec support, Multiple streaming
- Tampering, Motion detection, Defocus detection
- Micro SD / SDHC / SDXC memory slot (Max. 128GB)
- Hallway view, WiseStream II support
- LDC, PoE

Accessories (Optional)



SBP-120WMW



SBP-300WMW1



SBP-300CMW



SBP-300PMW



SBP-300KMW



SBP-300LMW



SBP-300NBW



SBP-300BW

| Video | |
|----------------------------|--|
| Imaging Device | 1/2.8" 5MP CMOS |
| Effective Pixels | 2592(H)x1944(V) |
| Min. Illumination | Color: 0.15Lux(F2.0, 1/30sec) |
| Video Out | HDMI: 1080p@30/25fps(60/50Hz) |
| Lens | |
| Focal Length (Zoom Ratio) | 2.8mm fixed focal |
| Max. Aperture Ratio | F2.0 |
| Angular Field of View | H: 104.4°/ V: 76.7°/ D: 136.1° |
| Focus Control | Fixed |
| Pan / Tilt / Rotate | |
| Pan / Tilt / Rotate Range | 0°~350° / 0°~69° / 0°~355° |
| Operational | |
| Camera Title | Displayed up to 85 characters |
| Day & Night | Auto(Electrical) |
| Backlight Compensation | BLC, WDR, SDR |
| Wide Dynamic Range | 120dB |
| Digital Noise Reduction | SSNR |
| Motion Detection | 4ea, polygonal zones |
| Privacy Masking | 6ea, rectangular zones |
| Gain Control | Low / Middle / High |
| White Balance | ATW / AWC / Manual / Indoor / Outdoor |
| LDC | Support |
| Electronic Shutter Speed | Minimum / Maximum / Anti flicker (1/5~1/12,000sec) |
| Video Rotation | Flip, Mirror, Hallway view(90°/270°) |
| Analytics | Defocus detection, Motion detection, Tampering |
| Business Intelligence | People counting |
| Alarm Triggers | Analytics, Network disconnect |
| Alarm Events | File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at event triggers |
| Network | |
| Ethernet | RJ-45(10/100BASE-T) |
| Video Compression | H.265/H.264: Main/High, MJPEG |
| Resolution | 2592x1944, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360 |
| Max. Framerate | H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 15fps/12fps(60Hz/50Hz) |
| Smart Codec | WiseStream II |
| Bitrate Control | H.264/H.265: CBR or VBR MJPEG: VBR |
| Streaming | Unicast(6 users) / Multicast Multiple streaming(Up to 3 profiles) |

| | |
|-----------------------------------|---|
| Protocol | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP |
| Security | HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) |
| Edge Storage | Micro SD/SDHC/SDXC 1slot 128GB |
| Application Programming Interface | ONVIF Profile S/G/T SUNAPI(HTTP API) Wisenet open platform |
| Web Viewer | Supported OS: Windows 7, 8.1, 10, Mac OSx10.12, 10.13, 10.14 Recommended Browser: Google Chrome Supported Browser: MS Explore11, MS Edge, Mozilla Firefox(Window 64bit only), Apple Safari(Mac OSxonly) |
| Memory | 512MB RAM, 256MB Flash |
| Environmental | |
| Operating Temperature / Humidity | -10°C ~ +40°C(-14°F ~ +104°F) / Less than 90% RH |
| Storage Temperature / Humidity | -30°C ~ +60°C(-22°F ~ +140°F) / Less than 90% RH |
| Certification | IP42, IK08 |
| Electrical | |
| Input Voltage | PoE(IEEE802.3af, Class2) |
| Power Consumption | PoE: Max 5.00W, typical 4.00W |
| Mechanical | |
| Color / Material | White / Plastic |
| RAL Code | RAL9003 |
| Product dimensions / weight | Ø99.0x56.0mm(Ø3.9x2.2"), 165g(0.36 lb) |
| DORI | |
| Detect (25PPM/ 8PPF) | 40.2m(12.26ft) |
| Observe (63PPM/ 19PPF) | 16.1m(4.90ft) |
| Recognize (125PPM/ 38PPF) | 8.0m(2.45ft) |
| Identify (250PPM/ 76PPF) | 4.0m(1.23ft) |

- The latest product information / specification can be found at hanwha-security.com
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.

