

ExCam XPT Q6075 Explosion-Protected PTZ Camera

Real-time movement and control in hazardous areas

Certified (ATEX, IECEx, EAC Ex and IA) for use in potentially combustible environments, ExCam XPT Q6075 offers HDTV 1080p and 40x optical zoom for great overview and excellent detail. Featuring Axis Lightfinder 2.0, it captures images with more realistic and saturated colors and sharper images of moving objects. It includes autotracking 2 with click and track functionality for active object tracking, and orientation aid with support for dynamic overlays for quick orientation. Enhanced security features such as signed firmware and secure boot ensure the integrity and authenticity of the firmware. Furthermore, Axis Zipstream with support for H.264/H.265 significantly lowers bandwidth and storage requirements.

- > **HDTV 1080p at 50/60 fps, with 40x optical zoom**
- > **Axis Lightfinder 2.0**
- > **Autotracking 2 and orientation aid**
- > **TPM, FIPS 140–2 level 2 certified**
- > **ATEX, IECEx, EAC Ex and IA; Zone 1, 21**



ExCam XPT Q6075 Explosion-Protected PTZ Camera

Camera		Scheduled and recurring: scheduled event Video: live stream open
Image sensor	1/2.8" progressive scan RGB CMOS	
Lens	4.25-170 mm, F1.6-4.95 Horizontal field of view: 65.1°-2.0° (1080p) Vertical field of view: 39.1°-1.18° (1080p) Autofocus, auto-iris	Event actions Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap PTZ: PTZ preset, start/stop guard tour File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.1 lux at 30 IRE, F1.6 B/W: 0.002 lux at 30 IRE, F1.6 Color: 0.15 lux at 50 IRE, F1.6 B/W: 0.003 lux at 50 IRE, F1.6	Data streaming Event data
Shutter time	1/11000 s to 1/3 s	Built-in installation aids Pixel counter, leveling guide
Pan/Tilt/Zoom	Pan: 360° endless, 0.05°-450°/s Tilt: 180°, 0.05°-450°/s Zoom: 40x optical, 12x digital, Total 480x zoom E-flip, 256 preset positions, tour recording (max 10, max duration 16 minutes each), guard tour (max 100), control queue, on-screen directional indicator, orientation aid PTZ, set new pan 0°, adjustable zoom speed, focus recall	General
Video		Casing IP66- and IP68-rated, ASTM 316L (EN 1.4404) stainless steel casing for maximum corrosion protection ^b
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Sustainability PVC free
Resolution	HDTV 1080p 1920x1080 to 320x180	Memory 1024 MB RAM, 512 MB Flash
Frame rate	Up to 50/60 fps (50/60 Hz) in HDTV 1080p	Power Camera: Power over Ethernet Plus (PoE+) IEEE 802.3at, Type 2 Class 4, typical 11 W, max 17.1 W Heaters: 24 V DC, max 60 W at -50 °C (-58 °F) AXIS T8154 60 W SFP Midspan: 100-240 V AC, max 74 W
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 and H.265	Connectors EXTB-3 Junction Box ExCam: 10 terminal clamps UT 2.5 2 conductor terminal USLKG 5.3 3 M20 cable entries
Image settings	Manual shutter time, compression, color, brightness, sharpness, WDR: up to 120 dB depending on scene, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, polygon privacy masks, image freeze on PTZ, automatic defog, backlight compensation, highlight compensation, electronic image stabilization	Storage Pre-installed AXIS Surveillance microSDXC Card 128 GB Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Network		Operating conditions -50 °C to 50 °C (-58 °F to 122 °F) (Intermittent up to 60 °C/140 °F) Humidity 10-100% RH (condensing)
Security	Password protection, IP address filtering, HTTPS ³ encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, protection of cryptographic keys with FIPS 140-2 certified TPM 2.0 module	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTPIC, LLDAP, MQTT, Syslog	Approvals EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11, EN 61000-6-2, EN 62479 Midspan EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR Explosion EN/IEC 60079-0:2012, EN/IEC 60079-1:2007, EN/IEC 60079-31:2009, TR CU 012/2011, GOST R IEC 60079-0-2011, GOST R IEC 60079-1-2011, GOST R IEC 60079-31-2010
System integration		Certifications Model key: T08-TNXCD-LLH-005.A-T ATEX: II 2G Ex d IIC T6 Gb, II 2D Ex tb IIIC T80°C Db Certificate: TÜV 18 ATEX 8218X IECEX: Ex d IIC T6 Gb, Ex tb IIIC T80°C Db Certificate: IECEX TUR 18.0023X EAC Ex: Ex d IIC T6 Gb, Ex tb IIIC T80°C Db Certificate: TC RU C-DE.AB.61.B.00381/19 IA: Ex d IIC T6 Gb, Ex tb IIIC T80°C Db Certificate: MASC MS/18-3256X EXTB-3 Junction Box ExCam: Model key: T12-3M20 ATEX: II 2 G Ex eb IIC T5 Gb, Ex II 2 D Ex tb IIIC T95°C Db IP66 Certificate: PTB 99 ATEX 3103 IECEX: Ex e IIC T5 Gb, Ex IIIC T95°C Db IP66 Certificate: IECEX PTB 06.0026 EAC Ex: 1Ex e IIC T5 Gb X, Ex tb IIIC T95°C Db X Certificate: RU C-DE.AA71.B.00120
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	Dimensions Height: 378 mm (14 7/8 in), ø 195 mm (7 11/16 in)
Analytics	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, autotracking 2, active gatekeeper Basic analytics (not to be compared with third-party analytics): object removed, enter/exit detector, object counter Supported Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Weight 20 kg (44.1 lb)
Event conditions	Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready	Included accessories Pre-connected 5 m (16 ft) ASKDP03-T Armoured Cable ExCam, AXIS T8154 60 W SFP Midspan, EXTB-3 Junction Box ExCam, AXIS Surveillance Card 128 GB, Installation guide, Windows [®] decoder 1-user license
		Optional accessories Wall mount ExCam XPT, Pole mount ExCam XPT Ex Connection Rail 4-port PoE Ex Connection Rail 8-port PoE SKDP03-T Cables ExCam 10 m (33 ft), 25 m (82 ft), 95 m (312 ft)

	ASKDP03-T Armoured Cable ExCam 10 m (33 ft), 25 m (82 ft), 95 m (312 ft)
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available on axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- b. *The camera has been developed in cooperation with SAMCON Prozessleittechnik GmbH*

Environmental responsibility:

axis.com/environmental-responsibility