

AXIS P7216 Video Encoder

Full-featured, cost-effective 16-channel video encoder

AXIS P7216 offers full-featured, efficient integration of analog cameras into an IP-based video surveillance system. It is ideal for large installations, especially where an IP network infrastructure is already in place. AXIS P7216 can be used as a standalone unit or be mounted in a 19" rack. It offers H.264 and Motion JPEG streams in all resolutions up to D1 (720x480 NTSC or 720x576 PAL). A single Ethernet port serves all 16 channels. The encoder offers video motion detection, active tampering alarm and two-way audio with audio detection. It comes with a power supply and has four built-in memory card slots for edge storage.

- > [Full frame rate](#)
- > [Edge storage](#)
- > [High resolution quad-view](#)
- > [Two-way audio](#)
- > [SFP slot - network redundancy](#)



AXIS P7216 Video Encoder

Video		Event actions	Pre- and post-alarm video buffering, video and audio recording to edge storage, play audio clip, external output activation File upload: FTP, HTTP, HTTPS, network share, email Notification: email, HTTP, HTTPS, TCP PTZ: PTZ preset
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline and Main Profiles Motion JPEG	Data streaming	Event data
Resolution	720x576 to 176x120 1536x1152 to 176x120 for quad view	Built-in installation aids	Pixel counter
Frame rate	25/30 fps (PAL/NTSC) Up to 15 fps in quad view in full resolution	General	
Video streaming	Multiple streams if identical or limited in frame rate/resolution Controllable frame rate and bandwidth VBR/CBR H.264	Casing	Standalone, metal casing, rack mount or wall mount
Image settings	Compression, color, brightness, contrast, text and image overlay, mirroring of images, privacy mask, aspect ratio correction, enhanced deinterlace filter, video termination, antialiasing, temporal noise filtering, rotation: 90°, 180°, 270°	Sustainability	PVC free
Pan/Tilt/Zoom	Wide range of analog PTZ cameras supported, drivers available for download at axis.com Support for one PTZ driver in each group of 4 channels Up to 100 presets per camera, guard tour, PTZ control queue Supports Windows® compatible joysticks	Memory	4x 512 MB RAM, 4x 128 MB Flash
Audio		Power	Axis PS-P power supply
Audio streaming	Two-way, full duplex, mic/line input 1 or 2/line output	Connectors	16x Analog composite video BNC inputs, NTSC/PAL auto-sensing 8x 3.5 mm audio input sockets 4x 3.5 mm audio output sockets 1x 1000 Base TX Ethernet (RJ45) 1x auxiliary Ethernet (RJ45) 1x Gbps SFP slot 4x Terminal block for up to 4 configurable external inputs/outputs 4x Terminal block for RS485/RS422 serial communication(full duplex) 1x DC input terminal block
Audio encoding	In AAC-LC 8 or 16 kHz 8–64 kbit/s G.711 μ-law PCM 8 kHz 64 kbit/s G.726 ADPCM 8 kHz 32 kbit/s or 24 kbit/s Out G.711 μ-law PCM 8 kHz 64 kbit/s μ-law PCM 16 kHz 128 kbit/s G.726 ADPCM 8 kHz 32 kbit/s or 24 kbit/s	Storage	Four microSD/microSDHC/microSDXC slots For SD card and NAS recommendations see axis.com
Audio input/output	External microphone input or line input Line level output Audio streaming, record (AU) and play uploaded (WAV, AU) clips AU (G.711 μ-law 8-bit 8/16 kHz mono), WAV (PCM 16-bit 8/16 kHz mono) 8 input, 4 output	Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 20–80% RH (non-condensing)
Network		Approvals	EMC EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2 C-tick AS/NZS CISPR 22 Class B, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, KCC KN22 Class B, KN24 Safety IEC/EN/UL 60950-1
IP address	Four IP addresses, one per four channels	Weight	1850 g (4.1 lb)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log	Included accessories	Mounting and connector kit (incl 2 mount brackets and 4 rubber feet) Power supply, installation guide, Windows® decoder license
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Optional accessories	For accessories, see axis.com
System integration		Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at axis.com/vms
Application Programming Interface	Open API for software integration, including VAPIX®, specifications at axis.com AXIS Guardian with One-Click Connection ONVIF® Profile S, specification at onvif.org	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Analytics	Included AXIS Video Motion Detection, active tampering alarm, audio detection	Warranty	5-year warranty, see axis.com/warranty
Event triggers	Analytics, external input, edge storage events, video loss	<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (eyay@cryptsoft.com).</p> <p>Environmental responsibility: axis.com/environmental-responsibility</p>	