

AXIS P1405-LE Mk II Network Camera

Compact, cost-effective HDTV surveillance with built-in IR

With Lightfinder and WDR – Forensic Capture, the bullet-style AXIS P1405-LE Mk II provides excellent image quality in HDTV 1080p resolution, even in complex light conditions. The built-in IR provides automatic illumination of a scene in complete darkness. AXIS P1405-LE Mk II supports Corridor Format for vertically oriented video stream of corridors, hallways or aisles. Furthermore, it features pixel counter, remote focus and zoom, as well as P-Iris control – ensuring optimal depth of field, resolution, image contrast and clarity. Axis' Zipstream technology significantly reduces bandwidth and storage requirements. The outdoor-ready camera comes with an adjustable weather shield.

- > [Lightfinder and WDR – Forensic Capture](#)
- > [Axis' Zipstream technology](#)
- > [HDTV 1080p at up to 30 fps](#)
- > [Built-in IR LED, 10 meters \(33 feet\)](#)
- > [Edge storage](#)



AXIS P1405-LE Mk II Network Camera

Camera		WDR mode
Image sensor	Progressive scan CMOS 1/2.8"	PTZ control, Overlay text IR illumination
Lens	2.8–10 mm, F1.6 Horizontal field of view 93°–32° Vertical field of view 51°–18° Varifocal, Autofocus, Remote focus and zoom, P-Iris control, IR corrected	Built-in installation aids
Day and night	Automatically removable infrared-cut filter	Pixel counter, Remote zoom (3.5x optical), Remote focus
Minimum illumination	Color: 0.18 lux at F1.6 B/W: 0.04 lux at F1.6 0 lux with IR illumination on	Data streaming
Shutter time	1/66500 s to 1 s	Event data
Video		General
Video compression	H.264 High, Main and Baseline profiles (MPEG-4 Part 10/AVC) Motion JPEG	Casing
Resolutions	HDTV 1080p 25/30 fps (WDR): 1920x1080 to 160x90 Meets relevant parts of SMPTE 274M (HDTV 1080p)	IP66, IP67- and NEMA 4X-rated casing (polyester polycarbonate blend)
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	Sustainability
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/MBR H.264 Axis' Zipstream technology in H.264	PVC free
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, White balance, Exposure control, Exposure zones, Fine tuning of behavior at low light, Text and image overlay, Privacy masks, IR illumination Wide Dynamic Range - Forensic Capture: Up to 120 dB depending on scene, Mirroring of images Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Memory
Pan/Tilt/Zoom	Digital PTZ	512 MB RAM, 256 MB Flash
Network		Power
Security	Password protection, IP address filtering, HTTPS ³ encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical: 4.6 W, max 11 W
Supported protocols	IPv4/v6, HTTP, HTTPS ³ , SSL/TLS ³ , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Connectors
System integration		RJ45 10BASE-T/100BASE-TX PoE
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com ONVIF Profile S, specification at www.onvif.org ONVIF [®] Profiles S and G, specifications at www.onvif.org	IR illumination
Analytics	Video Motion Detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	Built-in IR, highly efficient LED Range up to 10 m (33 ft)
Event triggers	Analytics Detectors: Day/Night Mode, Live Stream Accessed Tampering Hardware: Network, Temperature Input Signal: Manual Trigger, Virtual Inputs Storage: Disruption, Recording System: System Ready Time: Use Schedule, Recurrences	Storage
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
		Operating conditions
		-10 °C to 50 °C (14 °F to 122 °F) Humidity 10–100% RH (condensing)
		Storage conditions
		-40 °C to 65 °C (-40 °F to 149 °F)
		Approvals
		EN 61000-6-1, EN 61000-6-2, EN 50121-4, IEC 62236-4, EN 50581, EN 55024, EN 55032 Class A, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN-32 Class A, KN-35, IEC/EN/UL 60950-1, IEC/EN/UL 60950-2-2, IEC/EN 62471, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK08, NEMA 250 Type 4X, IEC 60825-1
		Weight
		With weather shield: 800 g (1.75 lb)
		Dimensions
		Ø132 x 260 mm (Ø5 3/16 x 10 1/4 in)
		Included accessories
		Mounting bracket, Drill template, Installation Guide, Windows decoder 1-user license AXIS Weather Shield L
		Optional accessories
		AXIS T94F01M J-Box/Gang Box Plate AXIS T91A47 Pole Mount AXIS T94P01B Corner Bracket AXIS T94F01P Conduit Back Box AXIS Weather Shield K Axis PoE Midspans For more accessories, see www.axis.com
		Video management software
		AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
		Languages
		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
		Warranty
		Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>
		Environmental responsibility: www.axis.com/environmental-responsibility