

# AXIS Q6215-LE PTZ Network Camera

## Heavy-duty PTZ camera with OptimizedIR

AXIS Q6215-LE PTZ Network Camera has a 1/2-inch sensor and combines great image quality with fast panning, tilting, and zooming. Its powerful, built-in IR illumination allows for an impressive viewing range in total darkness (up to 400 m or 1300 ft). This camera is ideal for open-area surveillance, since its robust design can withstand the toughest weather conditions including wind speed up to 245 km/h (150 mph). AXIS Q6215-LE is compliant with IP66, IP68, IK10, and NEMA 4X. It can be mounted facing up or down and comes equipped with a wiper to remove excess water, rain, or snow.

- > [HDTV 1080p with 30x zoom](#)
- > [Long-range OptimizedIR](#)
- > [MIL-STD-810G compliant](#)
- > [AXIS Guard Suite analytics](#)
- > [Zipstream, Lightfinder, and WDR](#)



# AXIS Q6215-LE PTZ Network Camera

<b>Camera</b>		PTZ: PTZ preset, start/stop guard tour, autotracking Overlay text, day/night mode
<b>Image sensor</b>	1/1.9" progressive scan RGB CMOS	<b>Data streaming</b> Event data
<b>Lens</b>	Varifocal, 6.7–201 mm, F1.6–5.3 Horizontal field of view: 58.6°–2.2° Vertical field of view: 34.1°–1.2° Autofocus, automatic day/night	<b>Built-in installation aids</b> Pixel counter Automatic orientation
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>General</b>
<b>Minimum illumination</b>	Color: 0.07 lux at 30 IRE F1.6 B/W: 0.008 lux at 30 IRE F1.6, 0 lux with built-in IR illumination Color: 0.1 lux at 50 IRE F1.6 B/W: 0.01 lux at 50 IRE F1.6, 0 lux with built-in IR illumination	<b>Cybersecurity</b> Signed firmware
<b>Shutter time</b>	1/30000 s to 1/6 s	<b>Casing</b> IP66-, IP68-, NEMA 4X- and IK10-rated aluminum casing Color: urban grey NCS S 5502-B Wiper included (silicone wiper blade)
<b>Pan/Tilt/Zoom</b>	Pan: 360° endless, 0.05°/s to 150°/s Tilt: -90° to +90°, 0.05°/s to 150°/s Zoom: 30x optical zoom, 21x digital zoom Preset accuracy: 0.10° 256 preset positions, tour recording, guard tour, control queue	<b>Sustainability</b> PVC free
<b>Video</b>		<b>Memory</b> 1024 MB RAM, 512 MB Flash
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), H.264 Main, High and Baseline Profiles Motion JPEG	<b>Power</b> High PoE 90 W midspan 1–port: 100–240 V AC, max 1.35 A Camera consumption: typical 25 W, max 71 W
<b>Resolution</b>	1920x1080 HDTV 1080p to 320x180	<b>Connectors</b> RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE
<b>Frame rate</b>	Up to 60/50 fps (60/50 Hz) in all resolutions	<b>IR illumination</b> Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 400 m (1300 ft) or more depending on the scene
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	<b>Storage</b> Support for SD/SDHC/SDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations, see <a href="http://axis.com">axis.com</a>
<b>Image settings</b>	Saturation, brightness, sharpness, noise reduction, WDR, white balance, day-night shift priority, exposure mode, manual shutter time, defogging, backlight compensation, highlight compensation, compression, fine tuning of low-light behavior, text and image overlay, privacy masks	<b>Operating conditions</b> -50 °C to 50 °C (-58 °F to 122 °F) Maximum temperature (intermittent): 60 °C (140 °F) Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10–100% RH (condensing) Wind load (sustained): 68 m/s (150 mph)
<b>Network</b>		<b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F)
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management	<b>Approvals</b> EMC EN 55032 Class A, EN 50121-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, NTCIP	<b>Safety</b> IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471 risk group 2 <b>Environment</b> IEC/EN 60529 IP66/IP68, NEMA 250 Type 4X, NEMA TS 2 (Subsection 2.2.7–2.2.9), IEC/EN 62262 IK10, MIL-STD-810G (Method 501.5, 502.5, 506.5, 509.5, 521.3), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
<b>System integration</b>		<b>Network</b> NIST SP500-267 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform, specifications at <a href="http://axis.com">axis.com</a> AXIS Guardian One-Click Connection ONVIF <sup>®</sup> Profile G and ONVIF <sup>®</sup> Profile S, specification at <a href="http://onvif.org">onvif.org</a>	<b>Dimensions</b> 210 x 330 x 313 mm (4 5/16 x 13 x 12 5/16 in)
<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection, AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard, active tampering alarm, gatekeeper <b>Supported</b> Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>	<b>Weight</b> 8.7 kg (19.3 lb)
<b>Event triggers</b>	Analytics, edge storage events, virtual inputs through API Detectors: day/night mode, live stream accessed, shock detection Hardware: fan, network, temperature Input Signal: virtual inputs, manual trigger PTZ: autotracking, error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: use schedule	<b>Included accessories</b> Installation Guide, Windows <sup>®</sup> decoder 1-user license, IK10 bumper, High PoE Midspan 1–port, RJ45 connector push pull plug
<b>Event actions</b>	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, and TCP	<b>Optional accessories</b> AXIS T95A64 Corner Bracket AXIS T98A15-VE Media Converter Cabinet A For more accessories, see <a href="http://axis.com">axis.com</a>
		<b>Video management software</b> AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
		<b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		<b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](http://openssl.org)), and cryptographic software written by Eric Young ([ey@cryptosoft.com](mailto:ey@cryptosoft.com)).

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)