

1.0 Manufacturer

Merit LILIN Ent. Co., Ltd.
No. 20, Wugong 6th Road,
Wugu District, New Taipei City 248

Manufacturer shall warrant the camera to be free from defects in material and workmanship for two years from the purchase date.

2.0 Camera Network Description

The Day & Night 1080P HD Dome IR IP Camera described shall be a LILIN model number LR2522E2/LR2522E4/LR2522E6 or equivalent. The camera described shall have high sensitivity megapixel camera using multiple-profile video streaming of H.264 and Motion JPEG technologies, built-in IR cut filter mechanism, auto color & mono switching, back light compensation, day & night applications for 24-hr surveillance, effective low light performance, and is PoE (IEEE 802.3af compatible) and/or can be directly powered using DC12V±10%.

3.0 General Specifications

- 3.1 The Day & Night 1080P HD Dome IR IP` camera shall incorporate a 1/2.5" Progressive scan CMOS sensor with 1920 (H) x 1080 (V) effective pixels. The network camera shall be able to produce images in 1080P, 720P, D1 or CIF resolution. The camera shall have a minimum light requirement of 0.5 Lux at F1.8 (Low Light Mode) /0.4 Lux at F1.6 (Low Light Mode) / 0.5 Lux at F1.8 (Low Light Mode) or 0 lux if IR LEDon.
- 3.2 The camera shall produce 15 frames per second at 1080P resolution with H.264 video compression or produce 15 frames per second at 1080P resolution with Motion JPEG video compression.
- 3.3 The camera shall provide three streaming at same time for various Internet or Intranet applications.
- 3.4 The camera shall provide Infrared LED for ultra low lux night vision.
- 3.5 The camera's projection beam of infrared LED shall reach 10M with IR wavelength at 850nm.
- 3.6 The camera shall have at least 256MB of RAM.
- 3.7 The camera shall provide a TCP/IP protocol video output via a RJ-45 Ethernet connection.
- 3.8 User and Administrator password protection levels are provided.
- 3.9 The camera shall provide two sets of sensors or video quality for day and night that the setting can be programmed based on individual schedule(s).
- 3.10 The camera is able to specify its shutter speed for min and max range for various environments. (1/30(25)s ~ 1/8000s)
- 3.11 The camera shall provide 3D noise reduction feature.
- 3.12 The camera shall provide WDR and BLC features.
- 3.13 The camera shall provide privacy mask features.
- 3.14 The camera shall provide motion and audio detection features.
- 3.15 The camera shall provide PoE (IEEE 802.3af compliant) input.
- 3.16 The camera shall provide video mirror and flip features.
- 3.17 A recessed mechanical rest button shall be provided to return the camera to factory default settings.

4.0 Camera Networking Requirements

- 4.1 The camera shall incorporate a built-in web server.
- 4.2 The camera shall provide integrated support for IP, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTCP, RTSP, Telnet, ICMP, IGMP, ONIVF Profile S, and SNM protocols.
- 4.3 The camera shall provide FTP services for sending JPEG snapshots based on scheduling and/or continuously sent with various time pattern, prefix, and postfix for JPEG file names that it can achieve better FTP system integration.
- 4.4 The camera shall provide email service for sending JPEG snapshots for at least 5 different recipients.
- 4.5 No unique or proprietary client software shall be required for viewing or controlling the camera.
- 4.6 The camera shall be user configurable and the administrator may functionally or aesthetically modify the camera’s web pages.
- 4.7 The camera shall provide 3G mobile remote live monitoring capability – Alarm PushVideo on smartphone devices.
- 4.8 Multiple cameras installed shall be connected and managed by Center Management Software (CMX/NAV software). Cameras can be grouped in the CMX/NAV Software. Camera groupings in CMX/NAV Software can be assigned for certain user(s) for user management purpose.
- 4.9 The camera shall provide IP filter to isolate a particular IP address for safety and related possible conditions.
- 4.10 The camera shall provide NTP (Network Time Protocol) feature so that the camera is able to connect to NTP network.
- 4.11 The camera shall provide OSD (on-screen display) feature which includes time display and device name display.
- 4.12 The Web server of the camera shall provide system log information for administrator(s) to view videos and operation details.
- 4.13 The camera shall provide alarm event notification via external alarm outputs on detections on audio, motion, and network lost.
- 4.14 The camera shall provide various alarm event outputs: i.e. GPIO (general purpose input/output), FTP (file transfer protocol) and email notification services to notify the users.

The camera shall not exceed a dimension of body: Ø 100 x 85mm, and weigh no more than 280g. Power requirement for the network camera shall be DC12V ±10% / PoE (IEEE 802.3af compliant). The operating temperature for video camera shall be -25°C ~ +50°C (-13°F ~ 122°F). The camera manufacturer shall be ISO 9001 certified and Camera shall comply with CE.

5.0 Minimum Performance Specifications

Day & Night 1080P HD Dome IR IP Camera				
Model		LR2522E2	LR2522E4	LR2522E6
Lens	Focal length	2.8mm	4mm	6mm
	Iris	F1.8	F1.6	F1.8

Angle of view	H	84°	62.2°	43.6°
	V	52°	37.4°	25.4°
	D	98°	69.2°	49.4°
Pick up element	1/2.5" CMOS image sensor			
Effective pixels	1920 (H) x 1080 (V) = 2,073,600 (pixel)			
Chip size	5.70mm (H) x 4.28mm (V)			
Scanning system	Progressive scan			
Infrared cut filter	Auto / Schedule / Day (Color) / Night (Mono)			
Min. Illumination	0.5 Lux at F1.8 (Low Light Mode) 0 Lux with IR LED on	0.4 Lux at F1.6 (Low Light Mode) 0 Lux with IR LED on	0.5 Lux at F1.8 (Low Light Mode) 0 Lux with IR LED on	
White balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Outdoor2			
Back light compensation	Off / On			
Electrical shutter	1/30s~1/8000s			
Sense Up	Off / 1 Frame / 2 Frames / 3 Frames / 4 Frames			
Sense Up+	Yes			
Auto gain control	36 dB variable gain			
3D noise reduction	Off / 1~32 selectable			
2D WDR	Off / On			
Privacy masking	Off / on (4 zones)			
Image effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip			
Audio in / output	Mono, 1.4 Vp-p, 50KΩ, Terminal connector			
Infrared LED	Peak wavelength	850nm		
	Beam spread	30°		
	Radiant distance	10M		
Operating temperature	-25°C ~ +50°C (-13°F ~ 122°F)			
Dimension	Ø100 x 85mm			
Weight	280g			
Power supply	DC12V±10% / PoE (IEEE 802.3af compliant)			
Power consumption	DC12V, 7.5W / PoE, 8.5W			
Network				
Video compression	H.264, Motion JPEG			
Resolution	1080P (1920 x 1080), 720P (1280 x 720), D1 (720 x 480), CIF (352 x 240)			
Maximum Frame Rate	H.264: up to 15 fps @ 1920 x 1080, 30 fps @ 1280 x 720, 30 fps @ 720 x 480			
	Motion JPEG: up to 15 fps @ 1920 x 1080, 30 fps @ 720 x 480, 30 fps @ 352 x 240			
Video streaming protocol	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast			

Video bitrate	128Kbps~5Mbps
	Frame rate and bit rate controllable on-the-fly
	VBR / CBR / GOP supported
Security	Base64 HTTP encryption
	Multiple user access levels with password protection
	10 user accounts available
Users	8 simultaneous users
Digital zoom	Yes
OSD	Text overlay for date, time, and camera name
Alarm functions	Alarm / motion / alarm detection triggering recording into SD card
	Image upload over FTP and email by audio / motion detection
CPU, memory	Embedded SoC ARM11, 528MHz, 256MB DDR2, 256MB flash memory
Maintenance	Firmware update via HTTP
	Firmware available at Website
Network Interface	10Mbps / 100Mbps Base-T, RJ-45
PC Requirement	OS: Windows 2000, Windows XP, Windows Vista, Windows 7, Windows 8
	Browser: Windows Internet Explorer 6.0 or above
	CPU: Intel Pentium 4 1.8GHz or above
	RAM: 1GB or above, Independent Display Card
Network Protocols	IP, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SNMP
Mobile Phone and PDA	iPhone, iPad, and Android support
System integration	ONVIF & LILIN HTTP API
Central management system	CMX3.6 / NAV 1.0 support
Video Display	LILIN Universal ActiveX & LILIN Java Applet
OS	Embedded Linux 2.6.32
Two-way audio	G.711 / PCM
SD card recording	Support Micro SD/SDHC card for circular recording (card is not included)
Alarm input / output	Digital 1 input (TTL, +3~5VDC) / 1 Output (MOS Relay contact N.O., Load max. 40VDC/300mA)

*Please submit ISO 9001, CE certificates.

*This specification is intended for use by the design/construction professional and any user of LILIN products to assist in developing project specifications for security and video surveillance systems.