



---

## HD 30M- IR Vari-focal Dome IP Camera



---

### Features

- IR cut filter for day/night operations
- 30-meter infrared night vision
- 1080p resolution @ 30 FPS
- High Dynamic Range
- Digital 1 input / 1 Output

---

### Description

As with all M series cameras, the MR2922AX HD 30M-Range IR Varifocal Dome IP Camera features 1080p at 30 frames per second, built-in Sense up+ technology to deliver stunning video in low-light conditions, and intelligent video surveillance (IVS) functions. Utilizing intelligent image signal processing, HDR, two-way audio, and 3D Noise Reduction, the combination successfully delivers the ultimate low-light image without motion blur. The support of PoE, privacy mask, and white balance, as well as the minimum illumination of 0.08 Lux at F1.4 will satisfy multiple applications.

## Specifications

Model	MR2922AX
Image Sensor/Sensor type	1/2.7" CMOS image sensor
Max. Image Pixels/ Total sensor pixels/ Effective Pixels	1920 (H) x 1080 (V) = 2,073,600 pixels
Video Compression	Smart H.264/ H.264 High/Main Profile, Motion JPEG
Megapixels	1080P(1920 x 1080) , 1280x960(1280 x 960) , 720P(1280 x 720) , D1(720 x 480, 720 x 576) , VGA (640 x 480) , CIF(352 X 240)
Frame Rates	H.264 : up to 30 FPS @ 1920 x 1080, MJPEG : up to 30 FPS @ 1920 x 1080
Lens/Focal length	2.8 – 12mm
Iris	F1.4
Angle of View	(H)102°– 34°(V)54°– 20°(D)122°– 39°
IR Radiant Distance	30m
Infrared LED Angle	60°, 90°
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.264 and Motion JPEG, configurable frame rate and bandwidth
Video bitrate	128Kbps – 12Mbps ; Frame rate and bit rate controllable on-the-fly VBR / CBR / GOP supported ; Fixed bitrate
Peak wavelength	850nm
Scanning System	Progressive scan
IR cut filter	Color (Day), Monochrome (Night), Auto, Schedule
Min. illumination/Low Light Mode (Colour)	0.08 Lux at F1.4 (Color) , 0.02 Lux at F1.4 (B/W) ; With Infrared LED 0 Lux
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Outdoor2

Back Light Compensation (BLC)	On / Off
Shutter Time	1/30(1/25)s to 1/30000s
Sense Up	Off / 1 frame / 2 frames
Sense Up+	Yes
Auto Gain Control	42 dB variable gain
3D Noise Reduction	Off / 1 to 32 selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode)
High Dynamic Range(HDR)	Up to 100dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	Off / On (4 independent areas)
D/N quality setting	Yes
Adjustable picture setting	Contrast, Brightness, Saturation
Other functions	Sharpness, Hue, Image flip, Image mirror
Lens distorsion correction (LDC)	Yes
Live video	CVBS 1.0Vp-p, 75 ohm, connector
Audio Input / Output	Mono, 1.98Vp-p, connector
Encryption	Base64 HTTP encryption / Digest
Access	Multiple user access levels with password protection
User accounts	10 user accounts available
IP address filter	Yes
Multi IP address	Yes
Users	10 simultaneous users
OSD (On-Screen Display)	Text overly for date, time , and camera name
IVS (Intelligent Video Surveillance)	Advanced motion detection, Tripwire detection, Semaphore + Tripwire detection, Object counting
Alarm event triggers	Motion/Tamper/Audio/Alarm/Network lost detection
Alarm event actions	FTP,SMTP, HTTP post, SD card, SAMBA
Alarm weighted mode	Yes
CPU	Embedded SoC ARM Cortex-A9, 600MHz, 256MB DDR3, 256MB flash memory
Firmware	Firmware upgrade via HTTP, and IP Scan
Network Interface/Ethernet	10Base-T / 100Base-TX, RJ-45

CE	Yes
FCC	Yes
Connectivity	ONVIF Profile S / LILIN API (CGI)
OS requirement	Windows 7, Windows 8, Windows 10
Web browser	Microsoft® Internet Explorer® 9.0 and later
CPU requirement	Intel i3 or above
RAM requirement	4GB or above, dedicated graphics card
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, SIP, MQTT, QoS, SNMP , SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SDDP, Bonjour
RTSP Authentication	On / Off
Mobile phone	Integrated to LILIN mobile app (LILIN Viewer) iPhone, iPad, Android support
Video Management	ONVIF Profile S / LILIN Navigator Enterprise 1.0 and 2.0 / Third party VMS through LILIN HTTP API
Video Display	LILIN Universal ActiveX , LILIN Java Applet & HTML5
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
OS	Embedded Linux 3.10
Audio	2-way audio supported , G.711 / PCM
SD Card (recording)	Support Micro SD/SDHC/SDXC (up to 128GB) card for circular recording (card is not included)
Alarm Input / output	Digital 1 input (TTL, +3 – 5VDC) / 1 Output (MOS Relay contact N.O., Load max. 40VDC/300mA), connector
Operating temperature	-25°C – +50°C (-13°F – 122°F)
Dimensions	Ø120mm x 115mm
Weight	510g approx.
Power Supply	DC12V ±10% , Power over Ethernet (IEEE 802.3af compliant)

---

PoE	IEEE 802.3af
Power Consumption	DC12V, 5.6W / PoE, 7.2W

---