



Outdoor HD 30M IR Range Fixed Dome IP Camera



Features

- Outdoor Vandal Dome Camera
- IR cut filter for day/night operations
- IP66 rain and dust resistant
- 30-meter infrared night vision
- 1080p resolution @ 30fps
- High Dynamic Range

Description

MR6322 HD 30M-Range IR Fixed Dome IP Camera in the M features 1080p at 30 frames per second, built-in Sense up+ technology to deliver stunning video in low-light conditions, and intelligent video surveillance (IVS) functions. Utilizing intelligent image signal processing, HDR, AGC control, and 3D Noise Reduction, the combination successfully delivers the ultimate low-light image without motion blur. The support of PoE,

privacy masking, white balance, as well as the minimum illumination 0.15 Lux at F2.0 can certainly satisfy multiple applications.

Specifications

Model	MR6322A
Image Sensor/Sensor type	1/2.7" CMOS image sensor
Max. Image Pixels/ Total sensor pixels/ Effective Pixels	1920 (H) x 1080 (V) = 2,073,600 pixels
Video Compression	Smart H.264/ H.264 High/Main Profile, Motion JPEG
Megapixels	1080P(1920 x 1080) , 1280x960(1280 x 960) , 720P(1280 x 720) , D1(720 x 480, 720 x 576) , VGA (640 x 480) , CIF(352 X 240)
Frame Rates	H.264 : up to 30 FPS @ 1920 x 1080, MJPEG : up to 30 FPS @ 1920 x 1080
Lens/Focal length	4mm
Iris	F2.0
Angle of View	(H)90°(V)45°(D)107°
IR Radiant Distance	30m
Infrared LED Angle	60°
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.264 and Motion JPEG, configurable frame rate and bandwidth
Video bitrate	128Kbps – 12Mbps ; Frame rate and bit rate controllable on-the-fly VBR / CBR / GOP supported ; Fixed bitrate
Peak wavelength	850nm
Scanning System	Progressive scan
IR cut filter	Color (Day), Monochrome (Night), Auto, Schedule

Min. illumination/Low Light Mode (Colour)	0.15 Lux at F2.0 (Color) , 0.05 Lux at F2.0 (B/W) ; With Infrared LED 0 Lux
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Outdoor2
Back Light Compensation (BLC)	On / Off
Shutter Time	1/30(1/25)s to 1/30000s
Sense Up	Off / 1 frame / 2 frames
Sense Up+	Yes
Auto Gain Control	42 dB variable gain
3D Noise Reduction	Off / 1 to 32 selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode)
High Dynamic Range(HDR)	Up to 100dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	Off / On (4 independent areas)
D/N quality setting	Yes
Adjustable picture setting	Contrast, Brightness, Saturation
Other functions	Sharpness, Hue, Image flip, Image mirror
Lens distorsion correction (LDC)	Yes
Audio Input / Output	Mono, 1.98Vp-p, Terminal Block
Encryption	Base64 HTTP encryption / Digest
Access	Multiple user access levels with password protection
User accounts	10 user accounts available
IP address filter	Yes
Multi IP address	Yes
Users	10 simultaneous users
OSD (On-Screen Display)	Text overly for date, time , and camera name
IVS (Intelligent Video Surveillance)	Advanced motion detection, Tripwire detection, Semaphore + Tripwire detection, Object counting
Alarm event triggers	Motion/Tamper/Audio/Network lost detection
Alarm event actions	FTP,SMTP, HTTP post, SD card, SAMBA
Alarm weighted mode	Yes

CPU	Embedded SoC ARM Cortex-A9, 600MHz, 256MB DDR3, 256MB flash memory
Firmware	Firmware upgrade via HTTP, and IP Scan
Network Interface/Ethernet	10Base-T / 100Base-TX, RJ-45
CE	Yes
FCC	Yes
Connectivity	ONVIF Profile S / LILIN API (CGI)
OS requirement	Windows 7, Windows 8, Windows 10
Web browser	Microsoft® Internet Explorer® 9.0 and later
CPU requirement	Intel i3 or above
RAM requirement	4GB or above, dedicated graphics card
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, SIP, MQTT, QoS, SNMP , SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SDDP, Bonjour
RTSP Authentication	On / Off
Mobile phone	Integrated to LILIN mobile app (LILIN Viewer) iPhone, iPad, Android support
Video Management	ONVIF Profile S / LILIN Navigator Enterprise 1.0 and 2.0 / Third party VMS through LILIN HTTP API
Video Display	LILIN Universal ActiveX , LILIN Java Applet & HTML5
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
OS	Embedded Linux 3.10
Audio	2-way audio supported , G.711 / PCM
SD Card (recording)	Support Micro SD/SDHC/SDXC (up to 128GB) card for circular recording (card is not included)
Alarm Input / output	Digital 1 input (TTL, +3 – 5VDC) / 1 Output (MOS Relay contact N.O., Load max. 40VDC/300mA), Terminal Block

IP Rating	IP66 waterproof
Vandal Resistant Rating / IK Rating	IK10
Operating temperature	-40°C - +50°C (-40°F - 122°F)
Dimensions	110mm x 89mm approx.
Weight	520g
Power Supply	DC12V ±10% , Power over Ethernet (IEEE 802.3af compliant)
PoE	IEEE 802.3af
Power Consumption	DC12V, 4.7W / PoE, 5.8W
