



## WALL, PENDANT & TOWER MOUNT BRACKETRY

The following range of bracketry has been designed specifically to be used with both analogue and IP cameras (VVRD, VPL7-WP-SM, VK2-VRD & VK2-60OPTZ) and is suitable for both external and internal applications.

With wall, pendant and tower mount options available, they all incorporate a new top hat design with a lip overlap to assist with any water drainage. The flat mounting plate and 4-point fixing makes camera connection very simple and can also accommodate a small amount of surplus cable, so provides added flexibility with ongoing maintenance. The large internal pipe diameter, allows any connections, including the RJ45 connector to be made and stored inside.

With the VRD-EWMB, there is a slight slope on the up stand reducing the chance of any standing water, should it make its way into the bracket from the back plate and can also be used in conjunction with the VDM-ECMA for corner mount applications. The VRD-EPMB pendant mount and VRD-TM tower mount bracket both have a 4" PCD to allow fitting to a majority of commercially available columns and towers.

To learn more about this product range please visit [vista-cctv.com](http://vista-cctv.com)



### Key Features:

#### Large diameter pipe

Allows connectors and any terminations to be pulled through and made inside

#### Simple camera connection

The new design top hat for makes for quick & simple installation on site and incorporates a lip to assist with water drainage

#### Powder coated

This allows the bracket suitable for both external and internal applications

## FLEXIBILITY BY DESIGN

## MODELS IN THIS RANGE:

0498930	VRD-EWMB	Wall bracket for VVRD, VPL7-WP-SM, VK2-VRD & VK2-600PTZ
0498940	VRD-EPMB	Pendant bracket for VVRD, VPL7-WP-SM, VK2-VRD & VK2-600PTZ
0498950	VRD-TM	Tower mount bracket for VVRD, VPL7-WP-SM, VK2-VRD & VK2-600PTZ

## ASSOCIATED PRODUCTS:

0457230	VDM-ECMA	Corner mount adaptor
0497240	VVRDE4V9CM-700	700TVL 4-9mm colour/mono vandal resistant dome
0497250	VVRDE4V9DN-700	700TVL 4-9mm day/night vandal resistant dome
0497260	VVRDE4V9DNLED-700	700TVL 4-9mm day/night LED vandal resistant dome
0474550	VPL7-WP-SM	700TVL 22:1 day/night IP66 vandal resistant fully functional 12/24 dome camera
0471750	VK2-540VRD	D1 4-9mm day/night vandal resistant PoE dome
0471740	VK2-2MPVRD	2MP 4-9mm day/night vandal resistant PoE dome
0473530	VK2-1080VRD	1080p 4-9mm day/night vandal resistant PoE dome
0473230	VK2-600PTZ	D1 (600TVL) 22:1 day/night IP66 vandal resistant fully functional 12VDC dome camera

## TECHNICAL SPECIFICATION

Model	VRD-EPMB	VRD-EWMB	VRD-TM
Type	Pendant	Wall	Tower
Construction	Mild steel		
Camera connection	4 x M5 (121.4mm PCD)		
Camera mounting plate	161 Ø mm		
Pipe internal	33mm Ø		
Pipe external	39mm Ø		
Mounting back plate	131 Ø x 3 (D) mm	160 (H) x 125 (W) x 3 (D) mm	127 Ø x 6 (D) mm
Mounting plate holes	4 x 10.5mm Ø (4"/ 101.6mm PCD)	4 x 10.5mm Ø (140 (H) x 84 (W) mm centres)	4 x 6.8mm slots (4"/ 101.6mm PCD)
Dimensions (net)	297 (H) x 161 Ø mm	250 (H) x 161 (W) x 325 (D) mm	410(H) x 161 (W) x 475 (D) mm
Dimensions (gross)	325 (H) x 175 (W) x 175 (D) mm	210 (H) x 370 (W) x 270 (D) mm	510 (H) x 435 (W) x 175 (D) mm
Weight (net)	1.3Kg	1.50Kg	2.2Kg
Weight (gross)	1.5Kg	1.9Kg	2.7Kg
Finish	Powder coated		
Colour	RAL7035		



No liability will be accepted by Vista for any errors or omissions in this information.  
Subject to change without notice.

VRD-Brackets-version1